

BASWA Disc DTG

2021/1



Product description and application areas

Insulation disc specially designed for BASWA acoustic systems for mechanical fastening of BASWA DTG acoustic panels to metal substructures.

Product details

Material	Galvanised steel
Article number	a 353
Diameter Ø	36 mm
Thickness	approx. 0.7 mm
Through hole Ø	approx. 5.5 mm
Consumption per m ²	12–15 Pcs./m²
Content/Packing	250/box
Weight	1 Pcs = approx. 3,5 g box of 250 pcs = approx. 880 g
Storage	Store dry protected from moisture

Delivery

Delivery information	Improper transport can cause damage. The goods must be protected
Delivery information	against mechanical influences and loads.

For further delivery information please BASWA acoustic AG, T +41 (0)41 914 02 22.

Disclaimer

The previously mentioned data, in particular the suggestions for the processing and application of our products, are based on our knowledge and experience in the normal case, prerequisite is that the products have been correctly stored and used. Because of the different materials, surfaces and deviating working conditions, no guarantee of the result of the work can be given, or liability be placed, regardless of the legal relationship, neither from these instructions, nor from verbal advice, unless we are culpable of intent or gross negligence. Hereby, the user must prove that he/she has provided punctual, complete written knowledge to BASWA in order for BASWA to attain a correct and successful evaluation. Upon receipt, the user must check the products for their suitability for the envisaged application. Changes to the product specifications remained reserved. Observe the protection rights of third parties. Furthermore, our respective sales and delivery conditions remain applicable. The current product data sheet is applicable and can be requested from us.