

BASWA Installation platform

2022/1



Product description and areas of application

The BASWA installation platform serves to accept built-in illuminators with expanding springs, as a stable basis for the attachment of elements such as monitoring cameras, fire alarms, loud-speaker boxes, heavy-duty ceiling lights and similar. The pressure-resistant characteristics of the installation platform prevent the edge spreading; thereby, there is no necessity to install wide, cover rings. The BASWA installation platform consists of an open-pore, pressure-resistant panel, has the same grade as the respective thickness of the BASWA acoustic panel and is available with or without an aperture.

Product data

Material	Plaster moulded panel (attachment/spacer frame) with 11 mm +/- 1 mm BASWA Phon coating
-----------------	--

Dimensiones	26 x 200 x 200 mm, bore of max. Dm 140 mm 26 x 300 x 300 mm, bore of max. Dm 230 mm 36 x 200 x 200 mm, bore of max. Dm 140 mm 36 x 300 x 300 mm, bore of max. Dm 230 mm 46 x 200 x 200 mm, bore of max. Dm 140 mm 46 x 300 x 300 mm, bore of max. Dm 230 mm
--------------------	--

66 x 200 x 200 mm, bore of max. Dm 140 mm
66 x 300 x 300 mm, bore of max. Dm 230 mm

BASWA IP DTG: 36 x 400 x 400 mm, bore of max. Dm 300 mm

Other dimensions on request (max. 1200 x 600 mm)

Delivery

Delivered as individual items

Application regulations

Installation

1. Attach the BASWA installation platform to the existing surface (adhere with sealant and attach with screws).
2. Place the BASWA acoustic panels tightly against the BASWA installation platform.
3. The surface preparation and BASWA coating in accordance with the respective applicable BASWA preparation directives.

General Instructions

For further information about safety during transportation, storage and handling, as well as disposal, refer to the BASWA safety data sheet (www.baswa.com).

Disclaimer

The previously mentioned data, in particular the suggestions for the processing and application of our products, are based on our knowledge and experience in the normal case, prerequisite is that the products have been correctly stored and used. Because of the different materials, surfaces and deviating working conditions, no guarantee of the result of the work can be given, or liability be placed, regardless of the legal relationship, neither from these instructions, nor from verbal advice, unless we are culpable of intent or gross negligence. Hereby, the user must prove that he/she has provided punctual, complete written knowledge to BASWA in order for BASWA to attain a correct and successful evaluation. Upon receipt, the user must check the products for their suitability for the envisaged application. Changes to the product specifications remained reserved. Observe the protection rights of third parties. Furthermore, our respective sales and delivery conditions remain applicable. The current product data sheet is applicable and can be requested from us.