

BASWA DTG acoustic panel

01/2022





Product description and areas of application

Sound-absorbing acoustic panel for the BASWA DTG acoustic system for direct mounting on a CD substructure in accordance with EN 13964.

Product data

Material	Mineral wool with airtight foil on the back
Article number	a 009
Dimensions	60 cm x 120 cm (0,72 m ²)
Thickness	36 mm
Consumption per m ²	1.39 panels per m²
Weight	2.8 kg / panel
Density	approx. 100 kg/m³
Reaction to fire	A2-s1, d0 according to EN 13501-1
Thermal conductivity	0.040 W / m*K

Proportion of recycled materials approx. 80 %	
Storage	Protect from sunlight. Store in a dry and frost-free place. Goods are sensitive to impact. Protect from mechanical damage during storage and and do not place any load on them. Do not store panels unprotected outdoors.

Delivery

Delivery form	Pallet
Delivery information	Improper transport can lead to damage. The panels must be protected against mechanical impacts and loads.

For further delivery information please contact BASWA acoustic AG, T +41 (0)41 914 02 22.

Legal notice

The above information, in particular the suggestions for the processing and use of our products, are based on our expertise and experience in the normal case, provided that the products have been stored and applied properly. Because of the different materials, surfaces and different working conditions, no guarantee of a work result or a liability, no matter what legal relationship, can be inferred from these notes or from a verbal consultation, unless it can be shown that we have acted with intent or gross negligence. Here, the user must prove that he has provided BASWA with all the information required for a proper and promising assessment by BASWA, on time and in full. The user must test the products for their suitability for the intended purpose. The product specifications are subject to change without notice. The protective rights of third parties must be observed. In addition, our respective terms and conditions of sale and delivery apply. The latest product data sheet, which can be requested from us, applies.