



## BASWA Fill Core

2019/2

### Product description and application

The BASWA Fill Core consists of recycled lightweight material and is used as a filling coat of BASWA Core panels to create a homogeneous, even surface for the application of the base coat of the BASWA Core System. BASWA Core Fill is specially adapted to the BASWA Core System to ensure fast, simple and high-quality installation.

### Product details

<b>Material</b>	Coating compound that consists of polymeric binders with fillers (expanded glass) and various organic and inorganic additives.
<b>Article number</b>	a 040
<b>Grain size</b>	0.5 - 1.0 mm
<b>Consumption per m<sup>2</sup></b>	Depending on the condition of the substrate, the consumption can vary between 2.5 and 4.5 kg/m <sup>2</sup>
<b>Colour</b>	grey-white
<b>Weight / Content</b>	10.0 kg Netto
<b>Storage</b>	Protect from frost, keep original packaging Storage / transport temperature between +5°C and 30°C Protect from direct sunlight Store dry and on pallets Shelf life up to 3 months under optimal conditions

## Delivery

---

**Delivery format** buckets

---

**Delivery information** Improper transport can cause damage.

---

For further delivery information please contact BASWA acoustic AG, T +41 (0)41 914 02 22.

## Installation:

1. Mix the ready-to-use BASWA Core Fill with clean water to the required consistency. (The desired consistency is pasty, but not watery)
2. **IMPORTANT!** When installing both the BASWA Core and BASWA Phon Systems simultaneously, only fill the active BASWA Core surface with BASWA Core Fill. The adjoining BASWA Phon Panels must be filled with BASWA Fill at the butt joints.
3. Apply the BASWA Core Fill to the already glued BASWA Core surface using a stainless-steel trowel. Using the trowel, smooth the surface as neatly and evenly as possible.
4. Small irregularities in the BASWA Core tiles can thus also be compensated.
5. After allowing sufficient drying time, sand the surface flat. (Note drying time and room conditions)
6. Evenly apply 2 coats of the BASWA Sound Absorbing Plaster to the flat sanded surface in accordance with the BASWA Sound Absorbing Plaster application guidelines.

## Disclaimer

The previously mentioned data, in particular the suggestions for the processing and application of our products, are based on our knowledge and experience in the normal case, prerequisite is that the products have been correctly stored and used. Because of the different materials, surfaces and deviating working conditions, no guarantee of the result of the work can be given, or liability be placed, regardless of the legal relationship, neither from these instructions, nor from verbal advice, unless we are culpable of intent or gross negligence. Hereby, the user must prove that he /she has provided punctual, complete written knowledge to BASWA in order for BASWA to attain a correct and successful evaluation. Upon receipt, the user must check the products for their suitability for the envisaged application. Changes to the product specifications remained reserved. Observe the protection rights of third parties. Furthermore, our respective sales and delivery conditions remain applicable. The current product data sheet is applicable and can be requested from us.