



Product description and areas of application

In order to prevent uncontrolled fissuring, use a ceiling separation strip to encompass the coating substances of all BASWaphon acoustic surfaces from other adjacent surfaces and/or structural elements (wall connections, pillars, metal or wooden window or door frames and similar). Depending on the optical or structural-physical requirement, this can be carried out using a paper separation strip.

Product data

Material	Siliconized natron paper
Item number	a265
Width of separation strip	65 mm
Thickness of separation strip	0.13 mm
Colour	White
Weight/roll	0.380 kg

Delivery

Delivered as

rolls of 50 m

Application regulations

Installation

1. Adhere the ceiling separation strip to the adjacent surfaces and/or structural elements (wall connections, pillars, metal or wooden window or door frames and similar).
2. Process the BASWaphon acoustic panel and coatings to the ceiling strip in accordance with the BASWA processing directives.
3. When the BASWaphon final coating is dry, cut the ceiling separation strips flush to the bottom of the ceiling.

Disclaimer

The previously mentioned data, in particular the suggestions for the processing and application of our products, are based on our knowledge and experience in the normal case, prerequisite is that the products have been correctly stored and used. Because of the different materials, surfaces and deviating working conditions, no guarantee of the result of the work can be given, or liability be placed, regardless of the legal relationship, neither from these instructions, nor from verbal advice, unless we are culpable of intent or gross negligence. Hereby, the user must prove that he/she has provided punctual, complete written knowledge to BASWA in order for BASWA to attain a correct and successful evaluation. Upon receipt, the user must check the products for their suitability for the envisaged application. Changes to the product specifications remained reserved. Observe the protection rights of third parties. Furthermore, our respective sales and delivery conditions remain applicable. The current product data sheet is applicable and can be requested from us.