


## BASWA Inspection cover

2012/1



### Product description and areas of application

Inspection covers are used for installing in walls (prefabricated walls and facing panels) and suspended ceilings. They are suitable for all panel thicknesses from 10 to 25 mm. Inspection covers are finished with BASWA Phon coating material and have the same surface structure as the surrounding acoustic covering.

### Product data

<b>Basic form</b>	square
<b>Item number</b>	a318- a322
<b>Dimensions</b>	300 x 300 mm, 400 x 400 mm, 500 x 500 mm, 600 x 600 mm Other dimensions on request
<b>Material</b>	anodised aluminium frame
<b>Colour</b>	white
<b>Weight/unit</b>	depends on the dimensions

## Application Instructions

### Installation

Screw fittings: a minimum of 4 screws for each side of the frame for panel sizes < 400 x 400 mm, a minimum of 6 or 8 screws for panel sizes > 500 x 500 mm. There should be no panel joints in the area of the inspection covers. Installation is carried out either in the sub-structure or as a retrofit. The section to be cut out should be 10 mm larger than the inspection covers. Arrange the removable frames with CD profiles corresponding to the dimensions of the inspection cover, spacing between the section and the removable frame should be a maximum of 10 mm. Place the exterior frame of the inspection cover at the opening, rest it on the cover, align and securely attach using screws. Subsequently, insert the inner cover and make sure it closes.

### Important additional information

Inspection covers must be handled carefully and under no circumstances must they be deformed. At the edges, it is very important that the exterior area of the frame is airtight with the substrate, by using a vapour-barrier adhesive tape (this prevents air circulation which would lead to discoloration around the edges).

Detailed drawings will be supplied on request.

### Disclaimer

The aforementioned specifications, in particular the suggestions for processing and using our products, are based on our knowledge and experience in the normal case, prerequisite is that the products have been correctly stored and used. Due to the different materials, surfaces and deviating working conditions, no guarantee can be given for the result of the task or adhesion, irrespective from which legal aspect, neither from these instructions, nor from verbal advice, unless we are culpable of intentional or gross negligence. Hereby, the user must prove that he/she has punctually transferred all knowledge in writing to BASWA in order that BASWA can carry out a correct and complete evaluation. The user must check the products for suitability for the intended use. Changes to the product specifications remain reserved. Observe the property rights of third parties. Furthermore, our respective sales and delivery conditions are applicable. The current product data sheet is applicable and can be requested from us.