
D 061 en Installation of recessed lamps suspended

Important:

Cracks could form in longer lamp housings made of metal or aluminum, if they are heated excessively. In that case, a separation of the top coat from the lamp housing by a separating cut must be planned. (See diagram D 089 en)

Any and all penetrations of installations, as well as gaps for connections to building elements, must be sealed with vapor barrier adhesive tape before the application of the acoustic panels. Such seals prevent air circulation through the openpore acoustic system (prevention of partial dust deposits in the top coat).

- 1. BASWAphon Top surface layer
- 2. BASWAphon Base primary layer
- 3. BASWAphon Acoustic Panel
- Plaster adhesive
- Structural panel, e.g., Fermacell or plasterboard
- Lamp housing
- Severance cut
- Lamp cover
- Vapor barrier adhesive tape (air-tight)





BASWA acoustic AG Marmorweg 10 CH - 6283 Baldegg www.baswa.com

The structural, static and physical construction characteristics of BASWAphon acoustic systems can only be reached if the sole use and processing of BASWAphon system components according to processing guidelines is ensured.

Created Gabriell Gjonlleshaj	Date Aug. 31, 2010
Reviewed	Approved
Eric Sulzer	Guido Koch

Technical changes reserved. The then-current version applies. Our guarantee only applies to the flawless composition of our materials. Information regarding usage, amounts and versions is based on experience, which cannot be transferred to differing conditions without adjustments. The information included in the diagram complies with the current state of the art. However, it cannot contain the entirety of generally accepted rules of civil engineering, applicable standards, guidelines and technical rules. These must be observed appropriately, in addition to the processing regulations, by the person performing the work. All rights reserved. Changes, reprints and photomechanical, as well as electronic, reproduction, even in excerpts, require the explicit permission from BASWA acoustic AG, Marmorweg 10, 6283 Baldegg, Tel.: +41 41 914 02 22, Fax: +41 41 914 02 20. Shipment not via the specialized trade. According to our general terms and conditions, shipping and payment conditions (general terms and conditions, see www.baswa.com), only to certified processors.