


Edge formation (with edge protection profile PVC front side with plaster)

Important

The coloured paint on the vertical plaster front face should preferably be applied before the BASWA Phon top coat.

Apply the edge protection profile PVC White a027 for two layer systems "Classic" Base, Fine or Top directly onto the acoustic panels with spray adhesive (for base and final layer thickness Total approx. 3.5-4.0 mm). With single layer systems BASWA Base or Fine, the precoating must first be partially sanded back by 1.5 mm to the leg width (for final layer thickness approx. 1.5-2.0 mm).



- 1 BASWA Top - Finish coat
- 2 BASWA Base - Base coat
- 3 BASWA Phon - Acoustic panel
- 4 BASWA Fix K - Cement adhesive
- 5 Structural panel, plasterboard
- 6 Smooth plaster painted, exposed concrete or similar
- 7 BASWA edge protection profile PVC, white a027

The structural, static and physical construction characteristics of BASWA Phon acoustic systems can only be reached if the sole use and processing of BASWA Phon system components according to processing guidelines is ensured.

Technical changes reserved. The then-current version applies. Our guarantee only applies to the flawless composition of our materials. Information regarding usage, amounts and versions is based on experience, which cannot be transferred to differing conditions without adjustments. The information included in the diagram complies with the current state of the art. However, it cannot contain the entirety of generally accepted rules of civil engineering, applicable standards, guidelines and technical rules. These must be observed appropriately, in addition to the processing regulations, by the person performing the work. All rights reserved. Changes, reprints and photomechanical, as well as electronic, reproduction, even in excerpts, require the explicit permission from BASWA acoustic AG, Marmorweg 10, 6283 Baldegg, Tel.: +41 41 914 02 22, Fax: +41 41 914 02 20. Shipment not via trade. According to our general terms and conditions, shipping and payment conditions (general terms and conditions, see www.baswa.com), only to certified processors.



EN_DD_024s

Edge formation (with edge protection profile PVC front side with plaster)

Scale 1/1

Size A3

Date 03.2020 / ALV